TPI polytechniek bv

Abluftschächte
Ventilation chimneys

Abluftschächte

Die TPI Abluftschächte, produziert von REA-DAN, sind aus hochwertigem Polyurethan hergestellt und garantieren eine optimale Lüftungscharakteristik. Das TPI-Programm enthält alle notwendigen Teile für die Projektierung einer modernen Stallbe- und entlüftungs-anlage. Rohre, Regenhauben, Lufteinströmringe usw. sind aus Polyurethan hergestellt; die Dachdurchführplatten wurden zur Verbesserung der Stabilität aus Polyethylen produziert. Die Kombination mit einer Kunststoffschrumpf-hülse stellt die optimale Dachdurchfürung des Kamines und die Dachabdichtung sicher.

Technische Daten

* Rohre aus hochwertigem Polyurethan
* Alle Rohrsysteme sind lieferbar in den Maßen : Durchmesser 315 - 404 - 430 - 520 - 620 - 640 - 720 - 820 - 1010 mm
* Rohrelemente werden in Halbschalen je 1 m Länge angeliefert
* Rohrverbindung wird mit V2A-Bändern vorgenommen, d.h. schnelle, sichere Montage
* Wandstärke der Elemente = 25 mm
* Lieferbare Teile : Regenhaube, Milieuhauben, Einströmringe, Übergangsteile, Endstücke, Usw.
* Dachdurchführplatten aus PE für jedes Dachplattenprofil und Dachneigung
* Optimale Einbaumöglichkeiten für alle am Markt befindlichen Ventilatoren!

Ventilation chimneys

The TPI exhaust chimneys, manufactured by REA-DAN, are produced of a high-quality poly-urethane and assure an optimum ventilation-characteristic. The programm includes all parts which are required for the projection of a modern agricultural ventilation system. Tubes, raincaps, environmental caps, air-inlets etc. are produced of polyurethane, by which for the roof connection-plates for stability-reasons was chosen for polyethylene. In combination with a shrink-plate it assures a 100% roof connection and closure.

Technical details

* Tubes produced of high-quality polyurethane
* Tubes available in the diameters: 315 - 404 - 430 - 520 - 620 - 640 - 720 - 820 - 1010 mm
* Tube elements in 2 sections, supplied in lenghts of 1 mtr.
* Tube connection by means of stainless steel ring which assures a quick and professional assemblance
* Skin thickness = 25 mm
* Available parts : Raincaps, Environmental caps, Air guides, Transition rings, Endparts, etc.
* Roof connection-plates available for every roofsheet profile and roof inclination
* Optimum build-in possibilities for all available fan types!

TPI polytechniek bv

P.O.Box 2064 5260 CB Vught, Holland
Phone: (0)73-656 91 94 Fax: (0)73-656 69 33